



samlexamerica

10A



Battery Chargers Microprocessor Controlled

Model
BP-1210
10 Amps

Design Features

- Universal AC input power with Power Factor Correction
- High performance 3 stage charging
- Easy to read LED's for system status
- Advanced microprocessor controlled
- Fully automatic operation
- Reverse Polarity, Short Circuit, Over-load and ignition protection
- Light weight and compact

2 YEAR WARRANTY

MODEL NO.	BP-1210
INPUT VOLTAGE	88 ~ 264 VAC / 47 ~ 63 Hz
INPUT CURRENT	1.9 A Max
POWER FACTOR	PF: 0.98
OUTPUT VOLTAGE	14.4 VDC
OUTPUT CURRENT	10 A Max
OUTPUT POWER	144 W Max
OPERATING TEMPERATURE	-20°C to +50°C (Refer to output load de-rating curve)
SAFETY	IEC 60950-1 (2001 +A11)
EMC	EN55022: 2006 Class B, 61000-4-2 Edition 1.2 : 2001-04: IEC 61000-4-4:2004 61000-4-5 Edition 1.1 : 2001-04: IEC 61000-4-4:Edition 2.1 : 2004-11 61000-4-8 Edition 1.1 : 2001-03: IEC 61000-4-11: Second Edition : 2004-03 61000-3-2 2006 ; 61000-3-3: 1995+A1 : 2001+A2 :2005: EN55024 : 1998+A1: 2001+A2 : 2003
WEIGHT, LBS	2.2 lbs
WEIGHT, KG	1 kg
DIMENSIONS, INCHES (L x W x H)	8.26 x 3.34 x 1.96"
DIMENSIONS, MM (L x W x H)	210 x 85 x 50 mm

NOTE: Specifications are subject to change without notice