



## Automatic Switch Mode Battery Charger

Model  
SEC-2415A  
15 Amps

### Design Features

- Switch mode technology is used for high efficiency, lightweight and quiet operation
- User selectable AC input voltage – 120 or 230 VAC
- User selectable (by DIP switch) 2 or 3 stage charging to ensure rapid and safe charging of all types of lead acid batteries – Flooded, AGM, Gel Cell or batteries with an external load
- Fully automatic operation
- Can charge 3 banks of batteries simultaneously, no isolator necessary
- Ammeter and LED power status indicator
- Ideal for charging all types of 12 volt lead-acid batteries
- Protections: short circuit, over current, reverse battery connection

MODEL NO.	SEC-2415A
PRE-SET INPUT VOLTAGE	120 VAC
USER SELECTABLE INPUT VOLTAGE	230 VAC
INPUT FREQUENCY	50 - 60 Hz
OUTPUT VOLTAGE-BOOST DIP SWITCH SELECTABLE	28 VDC, or 28.8 VDC or disabled
OUTPUT VOLTAGE-FLOAT	27 VDC
OUTPUT AMPS	15 A
OPERATING TEMPERATURE RANGE	0 - 40° C
WEIGHT, LBS	6.4
WEIGHT, KG	2.9
DIMENSIONS, INCHES (L x W x H)	10.8 x 8.4 x 3.3
DIMENSIONS, MM (L x W x H)	273 x 214 x 82
PROTECTIONS	Short circuit, over current, reverse battery connection, over temperature
OUTPUT BANKS	3

NOTE: Specifications are subject to change without notice