

**SPECIFICATIONS**

CELL	Multicrystalline silicon solar cell 156mmx78mm	
No. of cells and connections	36(6x6)	
Dimension of module	987x540x35(mm)	38.9x21.3x1.38 (in )
Weight	6kg	13.21b

**Characteristics**

Model	SPM060P	SPM065P
Power at STC(Pm)	60W	65W
Maximum power voltage(Vpm)	17.3V	18.1V
Maximum power current(Ipm)	3.5A	3.69A
Open circuit voltage(Voc)	21.9V	22.0V
Short circuit current(Isc)	3.8A	3.9A
Tolerance	± 5%	± 5%
Module efficiency	11.25%	12.19%

STC: Temperature 25°C, Irradiance 1000W/m<sup>2</sup>, AM=1.5**Limits**


Operating temperature	-40 to +85°C
Maximum system voltage	1000V DC
Series fuse rating	12A

**Components & Mechanical Data**

Front Glass	3.2mm tempered
Junction Box	IP-65 rated
Frame	Anodized aluminum alloy type 6063-T5
Encapsulation Material	EVA(0.5±0.05mm thickness)
Back Foil	White TPT(0.32±0.03mm thickness)
Temperature Range	-40°C to +90°C
Max Load	5400Pa

**Temperature coefficient**

Nominal Operation Cell Temperature	48°C±2°C
Current temperature coefficient	0.06±0.01 %/K
Voltage temperature coefficient	- (78±10) mv/k
Power temperature coefficient	- (0.5±0.05) %/k

**Back of the module****IV CURVES**